



## Plicord® Con-Ag™ Water S&D

### APPLICATION:

A general purpose water suction and discharge hose for applications in medium- or heavy-duty operations such as construction or agriculture.

### CONSTRUCTION:

**TUBE:** Black Versigard® synthetic rubber

**COVER:** Black Versigard synthetic rubber (wrapped finish) with yellow spiral stripe

**REINFORCEMENT:** Spiral plied synthetic fabric with wire helix



**TEMPERATURE:** -40°F to 180°F (-40°C to 82°C)

**PACKAGING:** 100' lengths, coiled and polywrapped

**BRANDING:** Continuous spiral brand example "Con-Ag Water S&D by Goodyear™."

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.

**ORDER CODES:** 542-159

ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg./m.
1 1/4	31.8	1.69	42.9	125	0.86	4	102	29	737	0.66	0.98
1 1/2	38.1	1.93	49.0	125	0.86	4	102	29	737	0.76	1.13
2	50.8	2.45	62.2	125	0.86	7	178	29	737	1.03	1.53
2 1/2	63.5	3.02	76.7	100	0.69	10	254	29	737	1.51	2.25
3	76.2	3.51	89.2	100	0.69	14	356	29	737	1.76	2.62
4	101.6	4.55	115.6	75	0.52	18	457	29	737	2.46	3.66
6	152.4	6.61	167.9	75	0.52	24	610	29	737	4.68	6.96

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2010 Veyance Technologies, Inc. All Rights Reserved.