

PVC Hose

Kanline OR


Oil resistant PVC heavy-duty suction and discharge hose.

Temp. Range: -13°F to 140°F

Applications: Heavy-duty suction and discharge of light oils and animal fats.

Construction: Flexible oil-resistant PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Features: Lightweight and flexible. External helix provides for easy drag. Rated for both suction and discharge.



Inside Dia. Inches	Outside Dia. Inches	Pitch Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In Hg	Weight Lbs/Ft	Standard Length Ft
2	2.60	.43	4.0	80	28.0	.77	100
3	3.74	.59	6.3	80	28.0	1.48	100
4	4.84	.65	7.1	60	28.0	2.14	100

Kanline SR

Water suction and discharge hose for heavy-duty applications requiring combined vacuum and higher working pressures.

Temp. Range: -13°F to 140°F

Applications: Heavy duty suction and discharge hose for use in fish suction and rental/construction pumping.

Construction: Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Features: Lightweight and flexible. External helix provides for easy drag. Rated for both suction and discharge. Clear sidewall permits visual check of material flow.



Inside Dia. Inches	Outside Dia. Inches	Pitch Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In Hg	Weight Lbs/Ft	Standard Length Ft
1 1/2	2.03	.37	2.5	110	28.0	.47	100
2	2.60	.43	4.0	100	28.0	.70	100
3	3.70	.59	6.3	100	28.0	1.13	100
4	4.78	.65	7.1	75	28.0	1.74	100
6	7.17	.93	10.2	70	28.0	3.88	60,100
8	9.34	1.07	15.7	60	28.0	5.54	15,20,25
10	11.63	1.22	24.8	40	28.0	8.68	15,20,25
12	13.66	1.34	45.0	28	25.0	10.30	20

PVC Hose