



Spiraflex® Gray (Light Duty)

APPLICATION:

For light-duty water discharge service.

CONSTRUCTION:

TUBE: Black Pliovic™ compound

COVER: Gray Pliovic compound

REINFORCEMENT: Synthetic fabric



TEMPERATURE: -10°F to 150°F (-23°C to 66°C)

PACKAGING: 300' continuous one piece, coiled and banded

BRANDING: Continuous brand example "Goodyear™ Spiraflex Gray 2" (53.0 mm) 90 psi (.72 Mpa). Made in USA."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 537-555

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1 1/2	38.1	1.72	43.7	90	0.72	0.19	0.28
2	50.8	2.22	56.4	80	0.62	0.24	0.36
2 1/2	63.5	2.79	70.9	60	0.41	0.36	0.54
3	76.2	3.31	84.1	50	0.34	0.39	0.58
4	101.6	4.33	110.0	45	0.31	0.65	0.97
6	152.4	6.38	162.1	35	0.24	1.07	1.59

Note: Working pressures are rated at 72°F.

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2010 Veyance Technologies, Inc. All Rights Reserved.