



2006 M & M WATER TIGHT SHORT STARTER COUPLERS



2006 Part No.	Nom. Pipe O.D. (Z)	Length (X)	Ring O.D. (Y)	Carriage Bolt Size	No. of Bolts per Coupler	Weight
2006-03D	3.000"	10.000"	6.250"	3/8" x 2-1/2"	4	8 lbs.
2006-03I	3.500"		6.250"		4	8 lbs.
2006-04D	4.000"		7.250"		5	9 lbs.
2006-04I	4.500"		7.250"		5	9 lbs.
2006-05D	5.000"		8.188"		6	10 lbs.
2006-05I	5.563"		8.188"		6	10 lbs.
2006-06D	6.000"		8.250"		6	13 lbs.
2006-06I	6.625"		9.125"		7	13 lbs.
2006-06P	6.140"		8.750"		6	13 lbs.
2006-08D	8.000"		10.813"		8	17 lbs.
2006-08I	8.625"		11.375"		8	17 lbs.
2006-08P	8.160"		10.813"		8	17 lbs.
2006-10D	10.000"		12.813"		10	21 lbs.
2006-10I	10.750"		13.688"		10	21 lbs.
2006-10P	10.200"		12.813"		10	21 lbs.
2006-12D	12.000"		15.438"		12	24 lbs.
2006-12I	12.750"		15.875"		12	24 lbs.
2006-12P	12.240"		15.438"		12	24 lbs.
2006-14D	14.000"	17.000"	14	26 lbs.		
2006-15P	15.300"	18.250"	15	28 lbs.		
2006-16D	16.000"	19.000"	16	30 lbs.		
2006-180D	18.000"	12.000"	21.188"	3/8" x 3"	18	34 lbs.
2006-183P	18.360"		21.188"		18	34 lbs.
2006-187P	18.700"		21.750"		18	36 lbs.
2006-20D	20.000"		23.500"		20	38 lbs.
2006-20P	20.400"		23.500"		20	39 lbs.
2006-22P	22.047"		25.250"		22	49 lbs.
2006-24D	24.000"		28.000"		24	55 lbs.
2006-24P	24.803"		28.000"		24	55 lbs.
2006-27P	27.953"		31.500"		28	68 lbs.
2006-31P	31.496"		35.750"		1/2" x 4"	30

- Use E/G/S after Part # to indicate Epoxy/ Galvanized/ 304 Stainless Steel.
- Bodies are 11 GA. Material.
- Rings are 5/16" Thick on Carbon Steel 1/4" Thick on Stainless Steel.
- Pressure Rating of 150 PSI.